



Confidential 機密文件 非授權 請勿外流

Cable Range (for Sealing)	7.2 - 11.3 mm
Cable Range (for Anti-Pull)	9.8 - 11.3 mm
Working Temp.	-40°C to 105°C (-40°F to 221°F)
IP Ratings	IP68 - 10bar
Panel Mounting Hole	21.4 - 21.6 mm
UL File No.	E210562

REV:	DESCRIPTION	DATE
△	The end of the life cycle of the mold, the mold updates 模具壽命周期更新	2019/9
<b>AVC 全冠企業有限公司</b> AVC Industrial Corp.		
PRODUCT: NYLON CABLE GLANDS		
PART NO.: FGB21L-10G		
SCALE: 1:1	UNIT: mm	REV. 10.2

INSPECTED BY	PEACA	2021. 03. 11
DRAWN BY	JESSIE	2021. 03. 11
MATERIAL	B, D PART: BLACK UL EPDM A, C, F PART: GREY PA66 UL94V-2	

TOLERANCE:	6 ± 0.2	18.1~30 ± 0.5	<b>IP68</b>  <b>RoHS</b>
	6.1~9 ± 0.3	30.1~50 ± 0.6	
	9.1~18 ± 0.4	50.1~80 ± 0.8	
REMARK:	All rights reserved		
	( ) Inside reference value		