



Confidential 機密文件 非授權 請勿外流

Cable Range (for Sealing)	6.8 - 11.1 mm
Cable Range (for Anti-Pull)	9.6 - 11.1 mm
Working Temp.	-40°C to 105°C (-40°F to 221°F)
IP Ratings	IP68 - 10bar
Panel Mounting Hole	21.4 - 21.6 mm
AVC Test No.	TA128-110-0059
UL File No.	E210562

REV:	DESCRIPTION	DATE
△	The mold has been repaired and replaced with new parts 模具維護&更換新零件	2020/11
△	The end of the life cycle of the mold, the mold updates 模具壽命周期更新	2020/03

全冠企業有限公司
AVC Industrial Corp.

PRODUCT: NYLON CABLE GLANDS

PART NO.: FGB21S-10B

SCALE: 1:1 UNIT: mm REV. 6.1 F3A

INSPECTED BY	PEACA	2021.03.17
DRAWN BY	JESSIE	2021.03.17
MATERIAL	B, D PART: BLACK UL EPDM A, C, F PART: BLACK PA66 UL94V-2	

TOLERANCE:	6 ± 0.2 18.1~30 ± 0.5 6.1~9 ± 0.3 30.1~50 ± 0.6 9.1~18 ± 0.4 50.1~80 ± 0.8	PATENTED
REMARK:	All rights reserved () Inside reference value	IP68
		RoHS