



Confidential 機密文件 非授權 請勿外流

Cable Range (for Sealing)	7.8 - 12.0 mm
Cable Range (for Anti-Pull)	10.4 - 12.0 mm
Working Temp.	-40°C to 105°C (-40°F to 221°F)
IP Ratings	IP68 - 10bar
Panel Mounting Hole	21.7 - 21.9 mm
UL File No.	E210562

REV:	DESCRIPTION	DATE
△	The mold has been repaired and replaced with new parts 模具維護&更換新零件	2021/04
△	The mold has been repaired and replaced with new parts 模具維護&更換新零件	2020/11
AVC 全冠企業有限公司 AVC Industrial Corp.		
PRODUCT: NYLON CABLE GLANDS		
PART NO.: NPA21-10B+A		
SCALE: 1:1	UNIT: mm	REV. 5.2 F3A

INSPECTED BY	PEACA	2021. 05. 22
DRAWN BY	JESSIE	2021. 05. 22
MATERIAL	B, D PART: BLACK UL EPDM A, C, E, F PART: BLACK PA66 UL94V-2	

TOLERANCE:	6 ±0.2	18.1~30±0.5	PATENTED
	6.1~9±0.3	30.1~50±0.6	
	9.1~18±0.4	50.1~80±0.8	
REMARK:	All rights reserved		IP68 RoHS
	() Inside reference value		